

T-		
I01 (i3)	I01 (i3 REx)	I12 (i8)

SITUATION

Distribution of the following tool will be through the Automatic Tool Shipment Program. Additional tools may be purchased through your Regional Distribution Center (RDC). All prices in this bulletin are introductory prices and are only valid during the Automatic Tool Shipment.



Cable Strap Pliers Order P/N 83 30 2 359 966 Price - \$418.24

Cable strap pliers must be used whenever cable straps (zip ties) are being installed on the High-voltage system (HV). The cable strap pliers are designed to cut the strap flush, clean and straight without leaving sharp edges that can damage HV wires.



Torque Setting

- The appropriate ISTA repair manual section lists the cable strap pliers' torque setting for a particular repair, commonly referred to in ISTA as "Stage X" (X = the setting 0 to 8).
- Slide the lock (2) forward and hold.
- Turn the setting knob (1) to the appropriate setting number.
- Release the lock (2).



Cable Strap Application

- Set the pliers torque per the instructions above.
- Position the strap in the appropriate location by hand.
- Tighten the strap by hand so that one stroke of the cable strap pliers torques and cuts the strap.
- Slide the cable strap into the front of the cable strap pliers (1).
- The cable strap pliers should butt up against the cable strap lock.
- Squeeze the handle of the cable strap pliers until the strap is cut.
- For complete repair information on this tool, refer to ISTA repair manual section 61 27

SPECIAL TOOL WARRANTY INFORMATION

Refer to Parts Logistics bulletin B-32-0514-0604, page 7-8, for special tool warranty details.